

8991 PROLASER® ELECTROTA®



TECHNICAL DATA

- Accuracy: ± 0.1 mm/m (± 0.0001 in/in)
- Self-leveling: ±5°
- Self-leveling type: Electronic
- Manual leveling of up to $\pm 5^\circ$ in both X and Y planes for slopes and gradients
- Laser range with detector: 50 m (165 ft)
- Laser range with detector: 300 m (980 ft)
- Protective shock absorbing cover
- Durable handles
- 5 customizable rotation speeds:
- 0 (Stationary Point), 60,120, 300, 600 rpm
- 6 scan modes create visible laser lines for diverse applications
- Visual & audible "Out of Leveling Range" warning
- 5/8" tripod thread for flat & 90° mounting

APPLICATIONS

- Electrical
- Tilling
- Masonry
- Drywall Installation
- Woodworking

KIT INCLUDES

- Remote control
- Laser detector
- Beamfinder[™] glasses
- Laser target
- · Rechargeable batteries
- Battery charger
- 2 X battery brackets for regular & rechargeable batteries
- Shockproof protective case





WATER & DUST

RESISTANT

Kapro, the Kapro logo, Plumb Site® Dual-View™ vial, Swivel Plumb Site®, OPTIVISION® Red, Set & Match, Prolaser®, Shark, Postrite and Ergo Grip™ are trademarks and/or registered trademarks of Kapro Industries Ltd.